

SRGDP-TL means Semi-Rigid-Galvanized-Double Wall with a thermo-laminated membrane ovalized to 3.5 inches. FLIXS is an uninsulated semi-rigid galvanized steel ventilation duct designed to be used in structural concrete slabs. This patent-pending product has a thermolaminated polymer membrane on its exterior surface to eliminate contact between steel and concrete thereby eliminating the development of corrosion.

SRGDP-TL is manufactured from a double strip of galvanized steel 0.005" longitudinally profiled. The outer strip is contoured and allows the flexible structure of the duct to be created. The inner membrane creates a perfectly smooth surface and is simultaneously assembled into complex 7 facet joints. This seven-facet joint provides a perfect seal at the operating pressure shown in the table below while eliminating water leaks generated by condensation.

- The interior surface of the SRGDP-TL is smoother than all ducts on the market;
- The duct does not deform and thus keeps the circular surface even when it is bent at 90 degrees, limiting static loss;
- No screws are required, eliminating debris buildup;
- Sloping installation is possible allowing the elimination of condensation;
- Conduit manufactured in one length without seal eliminating any possibility of water leakage;
- Thermolaminated polymer membrane;
- The duct is ovalized at 3,5 inches;

SRGDP-TL is easily foldable allowing 90-degree elbows to be formed. This product has a high seal and makes it possible to adapt to all types of systems both in terms of temperatures in heating mode and those in cooling mode.

SRGDP-TL is very robust and resists without warping when installed in a concrete slab.

Bending diameter: 1.5 - 2 times the diameter of the duct

Galvanized steel: 4"

Maximum length of 50 "or custom accepted

Materials available	Galvanized steel
Flame spread*	<0
Fume development*	<0
Maximum air velocity	4000 ft/min
Positive operating pressure in continuous mode	15" of WC
Negative operating pressure in continuous mode	15" of WC
Operating temperature amplitude	-60 ⁰ to 75 ⁰ Celsius
Duct wall thickness	0.01" (0.26mm)

When the duct is buried in a standard concrete slab



Ce produit est certifié

CAN/ULC S115-18
ASTM E814-24

intertek
Total Quality. Assured.

Project number : G105817069